

**FORTEX®****REFERENCIA**

441180000

**CÓDIGO EAN**

8423640055056

**ARTÍCULO**

Lathe ftx-550x250-to \* 230v-f1 with bench

**DESCRIPCIÓN**

Lathes to work metals, professional use, robust design with laminated and rectified prismatic guides. With a shaft of guide for automatic advances. Changing speeds by belts. Stopper microswitch by opening pulley cap or plate protector. Clipping plate protector and turret. Emergency stop Automatic thread change. Machines manufactured according to EC standards.

**ARTÍCULO**

Lathe ftx-550x250-to \* 230v-f1 with bench

**DATOS TÉCNICOS**

Coordinate viewer X/Y	NO
Alimentación	230V/F1
Potencia	0.75 - 1 Kw-Hp
Change speeds	STRAPS
Diameter on bench	250 mm.
Diameter on neckline	- mm.
Diameter on cart	145 mm.
Banking width	132 mm.
Inner diameter spindle	26 mm.
Distance between points	550 mm.
Point	MT4
Cone contrapoint	MT2
Diameter counterpoint	30 mm.
Tour counterpoint	70 mm.
Número de velocidades	6
Rango velocidades	125 - 2000 r.p.m.
Longitudinal forward range	0.07 - 020 mm / rev.
Cross-sectional forward range	- mm/rev.
A. Rapid longitudinal intermediate car	- m/min.
A. Cross-sectional carriage	- m/min.
Range metric steps	18 TIPOS / 0.2 - 3.5 mm.
Rank inches	21 TIPOS / 8 - 56 tpi
Range diametric steps	- d.p.
Range modular steps	- m.p.
Peso Neto/Bruto	130 Kg.
Dimensiones	1155x560x565 mm.