

FORTEX**REFERENCIA**

441110000

CÓDIGO EAN

8423640093256

ARTÍCULO

LATHE FTX-750X250-TO VARIO *230V/F1 *1,1KW WITH PEDESTAL LUXE

DESCRIPCIÓN

Two speed bands allow maximum tightening at lower speeds. Guides in double V, tempered and rectified. Precision ring on conical bearings. Adjustable counters in guides. Easy counterpoint and cylinder compensation marked in metric and inches. Reversible engine. Reversible thread bar for left-hand threading. Dial thread indicator. Tail and turret dish protector. Emergency stop. Microinterruptor stop by opening of pulley cover or protective dish. Machines manufactured according to CE standards.

ARTÍCULO

LATHE FTX-750X250-TO VARIO *230V/F1 *1,1KW WITH PEDESTAL LUXE

DATOS TÉCNICOS

Coordinate viewer X/Y	NO
Alimentación	230V/F1
Potencia	1,1 - 1,5 Kw-Hp
Change speeds	VARIABLE
Diameter on bench	250 mm.
Diameter on neckline	- mm.
Diameter on cart	140 mm.
Banking width	132 mm.
Inner diameter spindle	26 mm.
Distance between points	750 mm.
Point	MT4
Cone contrapoint	MT2
Diameter counterpoint	30 mm.
Tour counterpoint	70 mm.
Número de velocidades	2 - VARIABLE
Rango velocidades	50 - 2000 r.p.m.
Longitudinal forward range	0.07 - 0.40 mm/rev.
Cross-sectional forward range	- mm/rev.
A. Rapid longitudinal intermediate car	- m/min.
A. Cross-sectional carriage	- m/min.
Range metric steps	18 TIPOS / 0.2 - 3.5 mm.
Rank inches	21 TIPOS / 8 - 56 tpi
Range diametric steps	- d.p.
Range modular steps	- m.p.
Peso Neto/Bruto	140 Kg.
Dimensiones	1500X560X570 mm.