

FORTEX®**REFERENCIA**

441105000

CÓDIGO EAN

8423640093324

ARTÍCULO

LATHE FTX-700X280-TO VARIO*230V/F1*1,5KW +PEDESTAL LUXE (BL)

DESCRIPCIÓN

Automatic progression of the longitudinal and transversal car. Guides in double V, temperate, and rectified. Precision ring on conical bearings. Adjustable counters in guides. Easy counterpoint and cylinder compensation marked in metric and inches. Separate threaded bar for threading functions. Reversible engine. Reversible thread bar for left-hand threading. Great intermediate trolley with two T slots. Stopper microinterruptor by opening of pulley cover or plate protector. Tail and turret dish protector. Emergency stop. Dial thread indicator. Machines manufactured according to CE standards.

ARTÍCULO

LATHE FTX-700X280-TO VARIO*230V/F1*1,5KW +PEDESTAL LUXE (BL)

DATOS TÉCNICOS

Coordinate viewer X/Y	NO
Alimentación	230V/F1
Potencia	1,5 - 2 Kw-Hp
Change speeds	VARIABLE
Diameter on bench	280 mm.
Diameter on neckline	- mm.
Diameter on cart	165 mm.
Banking width	165 mm.
Inner diameter spindle	38 mm.
Distance between points	700 mm.
Point	MT5
Cone contrapoint	MT3
Diameter counterpoint	30 mm.
Tour counterpoint	80 mm.
Número de velocidades	2 - VARIABLE
Rango velocidades	50 - 2000 r.p.m.
Longitudinal forward range	0.07 - 0.40 mm/rev.
Cross-sectional forward range	0.02 - 0.28 mm/rev.
A. Rapid longitudinal intermediate car	- m/min.
A. Cross-sectional carriage	- m/min.
Range metric steps	18 TIPOS / 0.2 - 3.5 mm.
Rank inches	21 TIPOS / 8 - 56 tpi
Range diametric steps	- d.p.
Range modular steps	- m.p.
Peso Neto/Bruto	230 Kg.
Dimensiones	1400X700X680 mm.