

AFORTEX®**REFERENCIA**

441085000

CÓDIGO EAN

8423640961753

ARTÍCULO

FTX-914X300-TO T *400V/F3 with bench and accessories

DESCRIPCIÓN

Screw to work metals, professional use, robust design with prismatic guides laminated and rectified, with rear protector, cooling pump, foot brake, automatic gearbox bathed in oil. Spindle with conical roller bearings, adjustable wedge-shaped chariots. Microinterruptor stop by opening of pulley cover or protective dish. Tail and turret dish protector. Emergency stop. Automatic longitudinal and transverse movement. Dial thread indicator. Race top longitudinal advancement of the car. Machines manufactured according to CE standards.

ARTÍCULO
FTX-914X300-TO T *400V/F3 with bench and accessories
DATOS TÉCNICOS

Coordinate viewer X/Y	NO
Alimentación	400V/F3
Potencia	1.1 - 1.5 Kw-Hp
Change speeds	ENGRATMENTS
Diameter on bench	300 mm.
Diameter on neckline	430 mm.
Diameter on cart	190 mm.
Banking width	180 mm.
Inner diameter spindle	38 mm.
Distance between points	914 mm.
Point	MT5
Cone contrapoint	MT3
Diameter counterpoint	32 mm.
Tour counterpoint	90 mm.
Número de velocidades	18
Spindle speed range	65 - 1810 r.p.m.
Longitudinal forward range	0.079 - 1,291 mm/rev.
Cross-sectional forward range	0.017 - 0.276 mm/rev.
A. Rapid longitudinal intermediate car	- m/min.
A. Cross-sectional carriage	- m/min.
Range metric steps	36 TIPOS / 0.4 - 7 mm.
Rank inches	36 TIPOS / 4 - 60 tpi
Range diametric steps	- d.p.
Range modular steps	- m.p.
Peso Neto/Bruto	540 Kg.
Dimensiones	1850X750X1460 mm.