

FICHA TÉCNICA DE PRODUCTO





REFERENCIA

443717789

CÓDIGO EAN

8718375410974

ARTÍCULO

Air.55 Magnetic Drill Air.55

DESCRIPCIÓN

Pneumatic motor systemAutomatic lubrication systemSafety coverENGLISH WITHOUT SPARS (Explosion Insurance)Anti-static constructionGreat race to drill deeper holesAlso available with permanent magnet for tubes and flat material.Fault permanent magnets systemNo electricity is needed for the magnetic baseThere is no loss of magnetic grip due to the involuntary energy lossPowerful clamping in a wide range of steel thicknesses



FICHA TÉCNICA DE PRODUCTO





443717789



ARTÍCULO

Air.55 Magnetic Drill Air.55

DATOS TÉCNICOS	
Maximum pressure bar.	8 bar.
Air consumption	1.1 m3 / min.
Yellow strawberries	12 - 52 (HSS), 12 - 55 (TCT) Ø mm.
Drill	1 - 23 Ø mm.
Avellanado	10 - 55 Ø mm.
Tour Max.	167 mm.
Threaded	-
Magnet	183x100x55 mm.
Velocidad1	380 r.p.m.
Cone morse	MT3 19.05mm (3/4 ")
Magnetic retention capacity	8826 nm.
Net / crude weight	16.5 / 17.5 kg.