

FORTEX®**REFERENCIA**

441630100

CÓDIGO EAN

8423640200500

ARTÍCULO

Drill FTX-25TC Pro R + L 400V / F3 * P / Brackets Autom.

DESCRIPCIÓN

Speeds of vessel raps change desktop. Spindle mounted on ball bearings. Motors and resistant smelting pulleys. Displacement of the table by zipper. Turn the table on the 360° column. Tilt table $\pm 45^\circ$. R & L model turn inverter. Cover opening safety switch. Machines manufactured according to EC standards.

FORTEX®

REFERENCIA

441630100

ARTÍCULO

Drill FTX-25TC Pro R + L 400V / F3 * P / Brackets Autom.

DATOS TÉCNICOS

Alimentación	400V/F3
Potencia	1,1 - 1,5 Kw-Hp
Número de velocidades	12
Velocidad	280 - 2300 m.p.m.
Capacidad broca	25 mm.
Distancia portabrocas-columna	215 mm.
Distancia husillo-mesa	710 mm.
Distancia husillo-base	1230 mm.
Cono morse	MT3
Profundidad taladro	85 mm.
Diámetro columna	80 mm.
Dimensión mesa	290X290 mm.
Altura total	1690 mm.
Peso Neto/Bruto	180 Kg.
Dimensiones	- mm.