

**FORTEX®****REFERENCIA**

441630100

**CÓDIGO EAN**

8423640200500

**ARTÍCULO**

Drill FTX-25TC Pro R + L 400V / F3 \* P / Brackets Autom.

**DESCRIPCIÓN**

Speeds of vessel raps change desktop. Spindle mounted on ball bearings. Motors and resistant smelting pulleys. Displacement of the table by zipper. Turn the table on the 360° column. Tilt table  $\pm 45^\circ$ . R & L model turn inverter. Cover opening safety switch. Machines manufactured according to EC standards.

**FORTEX®**

**REFERENCIA**

441630100

**ARTÍCULO**

Drill FTX-25TC Pro R + L 400V / F3 \* P / Brackets Autom.

**DATOS TÉCNICOS**

Alimentación	400V/F3
Potencia	1.1 - 1.5 Kw-Hp
Número de velocidades	12
Velocidad	280 - 2300 m.p.m.
Capacidad broca	25 mm.
Distancia portabrocas-columna	215 mm.
Spindle-to-table distance	710 mm.
Spindle-to-base distance	1230 mm.
Cono morse	MT3
Profundidad taladro	85 mm.
Diámetro columna	80 mm.
Dimensión mesa	290X290 mm.
Altura total	1690 mm.
Peso Neto/Bruto	180 Kg.
Dimensiones	- mm.