FORTEX®



REFERENCIA	CÓDIGO EAN
441450000	8423640965225

ARTÍCULO

FTX-20-TFS VARIO 230V/F1 0,60KW

DESCRIPCIÓN

The column with a milano tail ensures the correct position of the head. Precision screw with conical bearings. Adjustable jackets to guides. Reversible motor (left-right turn). Better contact between pinecon and zipper that offers a precise machining. Head block, student and guides. Head bow +-90o. Digital Depth Viewer. Machines manufactured according to CE standards.

FORTEX®



REFERENCIA

441450000

ARTÍCULO

FTX-20-TFS VARIO 230V/F1 0,60KW

DATOS TÉCNICOS	
Alimentación	230V/F1
Potencia	1,1 - 1,5 Kw-Hp
Transmisión	Engranajes
Número de velocidades	VARIABLE
Velocidad	50 - 2250 m.p.m.
Capacidad máxima broca	20 mm.
Inclinación del cabezal	-
Capacidad de roscado	-
Diámetro columna	- mm.
Diámetro máximo de fresado vertical	16 mm.
Diámetro máximo de fresado horizontal	63 mm.
Distancia portabrocas-columna	170 mm.
Max. Distancia portabrocas-mesa	370 mm.
Avance husilo	- mm./r
Cono morse	MT2
Profundidad taladro	50 mm.
Recorrido longitudinal (X)	295 mm.
Recorrido transversal (Y)	160 mm.
Recorrido vertical (Z)	250 mm.
Tamaño ranura en T	3X12 mm.
Altura total	- mm.
Dimensión mesa	500X180 mm.
Dimensión base	- mm.
Peso Neto/Bruto	103 Kg.
Dimensiones	760X580X780 mm.