

FORTEX®**REFERENCIA**

441429000

CÓDIGO EAN

8423640093089

ARTÍCULO

Drill-Milling FTX-2-FTD 230V / F1 1,1KW / 1.5hp

DESCRIPCIÓN

Milling drills for professional use with: Laminated head guides in Milan tail with wedge-shaped adjustment strips. Laminated pyramidal table guides with wedge-shaped adjustment strips. LED display X, Y, X with magnetic scales. Safety cover cover. Milan tail with metallic protector. Inclination head + -90°. Machines manufactured according to EC standards.

FORTEX®
REFERENCIA

441429000


ARTÍCULO

Drill-Milling FTX-2-FTD 230V / F1 1,1KW / 1.5hp

DATOS TÉCNICOS

Alimentación	230V/F1
Potencia	1,1 - 1,5 Kw-Hp
Transmisión	Direct
Número de velocidades	Variable
Velocidad	100 - 2500 m.p.m.
Capacidad máxima broca	25 mm.
Inclinación del cabezal	90
Capacidad de roscado	-
Diámetro columna	- mm.
Diámetro máximo de fresado vertical	16 mm.
Diámetro máximo de fresado horizontal	63 mm.
Distancia portabrocas-columna	350 - 1600 mm.
Max. Distancia portabrocas-mesa	370 mm.
Avance husilo	- mm./r
Cono morse	MT3
Profundidad taladro	50 mm.
Recorrido longitudinal (X)	485 mm.
Recorrido transversal (Y)	140 mm.
Recorrido vertical (Z)	- mm.
Tamaño ranura en T	3X12 mm.
Altura total	- mm.
Dimensión mesa	700X180 mm.
Dimensión base	- mm.
Peso Neto/Bruto	123 kg.
Dimensiones	960X580X780 mm.