

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441355000

CÓDIGO EAN

8423640093201

ARTÍCULO

Ftx-45-TFS 400V / F3 Milling Drill

DESCRIPCIÓN (

Its large square smelter pedestal, ensures maximum rigidity. Articulated arm control box. The reduced tolerance of the head gears ensures a silent operation. Equipped with low voltage security circuit. Cover protector with disconnect. Correct elevation of the head by the guides with a Milano tail rectified. Elevation of the manual or motorized head. Table lock on X-Y axes. Against tapered cadas on axes X, Y, and Z. Huste of large diameter with conical bearings. Zipper and pinion calibrated for a precise advance. Spindle depth lock. Table with automatic range of variable speed. Refrigeration system. Inclination head + -90 $^{\circ}$. Machines manufactured according to EC standards.





☆ FORTEX®

REFERENCIA

441355000



ARTÍCULO

Ftx-45-TFS 400V / F3 Milling Drill

DATOS TÉCNICOS	
Feed	400v / f3
Power	1.1 - 1.5 kW-HP
Transmission	Gears
Number of speeds	12
Speed	75 - 3200 m.p.m.
Maximum capacity drill	40 mm.
Tilt of the head	-
Threading	-
Diameter column	- mm.
Maximum diameter of vertical milling	32 mm.
Maximum diameter of horizontal milling	80 mm.
Distance Caker-column	260 mm.
Max. Distance Cake-up-table	470 mm.
Hausyl advance	- mm./r
Cone morse	Mt4
Depth drill	120 mm.
Longitudinal tour (x)	560 mm.
Transversal tour (Y)	230 mm.
Vertical travel (Z)	300 mm.
Slot size in T	3x14 mm.
Total height	1750 mm.
Table	800x240 mm.
Base dimension	- mm.
Net / crude weight	580/640 kg.
Dimensions	1020x940x2100 mm.