

FORTEX®**REFERENCIA**

441290000

CÓDIGO EAN

8423640963160

ARTÍCULO

FTX-200-FC universal milling machine * 400V-F3

DESCRIPCIÓN

Aluminum alloy support arm. 3 axis DRO. High precision coordinate table with ball spindle. Milan tail column. Adjustable milling head. Equipped with centralized lubrication. Axes automatic X, Y, Z series mounted with 3 servomotors. Spindle protector with automatic disconnection. Changing mechanical speeds in the head, powerful milling. Table with additional support column, great load capacity and high precision. High quality electrical components Schneider. Machines manufactured according to EC standards.

FORTEX



REFERENCIA

441290000

ARTÍCULO

FTX-200-FC universal milling machine * 400V-F3

DATOS TÉCNICOS

Alimentación	400V/F3
Potencia	7,5 - 10 Kw-Hp
Transmisión	Engranajes
Número de velocidades	27
Visualizador de coordenadas X/Y/Z	SI
Avance de mesa (X,Y,Z)	10-1000 / 10-1000 / 5-500 mm / min
Avance rápido (x,y,z)	2200, 2200, 1100 mm / min
Capacidad máxima broca	13 - 28 mm.
Inclinación del cabezal	360 °
Diámetro máximo de fresado vertical	200 mm.
Diámetro máximo de fresado horizontal	200 mm.
Distancia portabrocas-columna	45 - 745 mm.
Max. Distancia portabrocas-mesa	50 - 550 mm.
Cono morse	7:24 ISO50
Recorrido longitudinal (X)	1200 mm.
Recorrido transversal (Y)	700 mm.
Recorrido vertical (Z)	500 mm.
Tamaño ranura en T	5x18 - 80 mm.
Dimensión mesa	1600x500 mm.
Peso Neto/Bruto	4200/4500 kg.
Dimensiones	2625x2460x2080 mm.