

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

551005225

CÓDIGO EAN

8423640161405

ARTÍCULO

Electric cylinder FTX-1550X110-CIM 400V / F3 2,2KW hardened rollers

DESCRIPCIÓN (

The plate cylinder is designed to offer Maximum precision, ease of use and security, becoming the ideal tool for work with Light and medium aluminum sheets or stainless steel. Featured features: Easy handling Thanks to the mobile control panel with push buttons. Conical bending device For greater versatility in the work. Manual fall end, which facilitates the extraction of the finished ferrule. SAE 1050 steel rollers hardened by induction, with quality certificate and high tensile strength. Two rollers powered By a single gearbox and gear system, guaranteeing power and efficiency. Main racks of spheroidal cast iron, which provide great robustness and durability. Main engine with brake system, which ensures precise control and greater security. Wire slots At the ends of the rollers, expanding the possibilities of use. Complies with the EC Security Directives, ensuring safe and reliable operation. This cylinder combines Technology, Resistance and precision, offering optimal performance in workshops and industrial environments.



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

551005225



ARTÍCULO

Electric cylinder FTX-1550X110-CIM 400V / F3 2,2KW hardened rollers

DATOS TÉCNICOS	
Feed	400V/F3
Power	2,2 - 3 Kw-Hp
Power rear roller	- Kw-Hp
Prevailing capacity	- mm.
Curved capacity	3 mm.
Useful length of work	1550 mm.
Diameter roller	110 mm.
Roller speed	3 r.p.m.
Diameter slots rod	4 / 7 / 9 / 13 mm.
Dimensions Product	2700X750X1000 mm.
Net / crude weight	1200 Kg.