

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

551030040

CÓDIGO EAN

8423640162105

ARTÍCULO

Hydraulic press horizontal 40 ton. FTX-40-PH * 400V * F3

DESCRIPCIÓN (

Designed to offer Maximum stability, precision and security, this solid work table supports loads much higher than the usual bending efforts, guaranteeing exceptional performance in demanding industrial environments. Main features: Robust structure: High strength work table, capable of supporting remarkable loads without deformations. Cylinder located under the table, free of annoying frames, which facilitates the use of tools and improves ergonomics for the operator. Forged steel cart With double slides, tempered and grinding, protected with scrapers to ensure precision and durability. Ideal for both prototypes and for production series, thanks to its versatile and reliable design. Hydraulic monoblock power unit, with possibility of pressure regulation. Adjustable advance rate by flow control valve. Matching pins in alloy steel, tempered and rectified, with a quick conical change system for a secure block. Electric control by pedal and safety timer with push button. Side tool shelves, spacious and practical. Movement of rollers with double pedal, for comfortable and safe handling. Micrometric regulation of the carrera via hydraulic valve with ruffles. Continuous regulation of races, even under high working pressure, allowing you to obtain the desired folding angle without the need for previous evidence.



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

551030040



ARTÍCULO

Hydraulic press horizontal 40 ton. FTX-40-PH * 400V * F3

DATOS TÉCNICOS	
Feed	380v-f3
Power	1.5 / 2,2 - 2/3 kW-HP
Maximum performance pressure	40 ton.
Max. Mobile punch blow	250 mm.
Progress speed and punch return	1750/2000 mm / min
Punch operating speed	470 mm.
Mobile pins and fixed height x 0	120xï55 / 63 mm.
Min. Axis base between mobile and fixed pins	120 mm.
Max. Base of the shaft between mobile and fixed pins	370 mm.
Max. Operating pressure on hydraulic circuit	250 bar.
Hydraulic oil dispenses	70 I.
Noise level	70 dB.
Net / crude weight	920 kg.
Dimensions	1200x700x950 mm.
Dimensions Workbench	620x1500x930 mm.