

FORTEX®**REFERENCIA**

441597000

CÓDIGO EAN

8423640134300

ARTÍCULO

Drill FTX-20S-VS VARIO 230V / F1 * P / AUTOMBROOTS.

DESCRIPCIÓN

- Belt transmission. • Spindle mounted on bearings to balls. • Motors and resistant castings pulleys. • Displacement of the table by zipper. • Turn from the table on the column of 360°. • Tilt table $\pm 45^\circ$. • Opening safety switch cover.
- Machines manufactured according to EC standards. • Speed regulation by variator Vector frequency. • Laser Pointer in Cruz • 230V single-phase feeding • Industrial three-phase motor controlled by The variator with single-phase feeding • Multichannel strap to improve the Traction and reduce the Supnor level. • Electronic speed control for save energy and greater control over machine. • LED lighting • High durability metallic buttons. • Tacometer LED
- Milimetric control of spindle down • Automatic chuck

FORTEX®

REFERENCIA

441597000

ARTÍCULO

Drill FTX-20S-VS VARIO 230V / F1 * P / AUTOMBROOTS.

DATOS TÉCNICOS

Alimentación	230V/F1
Potencia	0,75 - 1 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 700 / 0 - 3000 r/min.
Capacidad broca	20 mm.
Distancia portabrocas-columna	190 mm.
Distancia husillo-mesa	470 mm.
Distancia husillo-base	670 mm.
Cono morse	MT2
Profundidad taladro	80 mm.
Diámetro columna	73 mm.
Dimensión mesa	270x270 mm.
Altura total	1065 mm.
Peso Neto/Bruto	59/62 kg.
Dimensiones	895x490x345 mm.