

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441597000

CÓDIGO EAN

8423640134300

ARTÍCULO

Drill FTX-20S-VS VARIO 230V / F1 * P / AUTOMBROOTS.

DESCRIPCIÓN (

• Belt transmission. • Spindle mounted on bearings to balls. • Motors and resistant castings pulleys. • Displacement of the table by zipper. • Turn from the table on the column of 360 °. • Tilt table ± 45°. • Opening safety switch cover. • Machines manufactured according to EC standards. • Speed regulation by variator Vector frequency. • Laser Pointer in Cruz • 230V single-phase feeding • Industrial three-phase motor controlled by The variator with single-phase feeding • Multichannel strap to improve the Traction and reduce the Supnor level. • Electronic speed control for save energy and greater control over machine. • LED lighting • High durability metallic buttons. • Tacometer LED • Milimetric control of spindle down • Automatic chuck



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

441597000



ARTÍCULO

Drill FTX-20S-VS VARIO 230V / F1 * P / AUTOMBROOTS.

DATOS TÉCNICOS	
Feed	230v / f1
Power	0.75 - 1 kW-HP
Number of speeds	2 - Variable
Spindle	0 - 700 / 0 - 3000 r/min.
Drill	20 mm.
Distance Caker-column	190 mm.
Distance spindle-table	470 mm.
Distance Husillo-Base	670 mm.
Cone morse	Mt2
Depth drill	80 mm.
Diameter column	73 mm.
Table	270X270 mm.
Total height	1065 mm.
Net / crude weight	59 / 62 Kg.
Dimensions	895X490X345 mm.