

**FORTEX®****REFERENCIA**

441595000

**CÓDIGO EAN**

8423640134317

**ARTÍCULO**

Drill FTX-25C-VS VARIO 230V / F1 \* P / AUTOM BROCAS.

**DESCRIPCIÓN**

- Belt transmission. • Spindle mounted on bearings to balls. • Motors and resistant castings pulleys. • Displacement of the table by zipper. • Turn from the table on the column of 360 °. • Tilt table  $\pm 45^\circ$ . • Opening safety switch cover.
- Machines manufactured according to EC standards. • Speed regulation by variator Vector frequency. • Laser Pointer in Cruz • 230V single-phase feeding • Industrial three-phase motor controlled by The variator with single-phase feeding • Multichannel strap to improve the Traction and reduce the Supnor level. • Electronic speed control for save energy and greater control over machine. • LED lighting • High durability metallic buttons. • Tacometer LED
- Milimetric control of spindle down • Automatic chuck

**FORTEX®**

**REFERENCIA**

441595000

**ARTÍCULO**

Drill FTX-25C-VS VARIO 230V / F1 \* P / AUTOM BROCAS.

**DATOS TÉCNICOS**

Alimentación	230V/F1
Potencia	1,1 - 1,5 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 700 / 0 - 3000 r/min.
Capacidad broca	25 mm.
Distancia portabrocas-columna	215 mm.
Distancia husillo-mesa	685 mm.
Distancia husillo-base	1175 mm.
Cono morse	MT2
Profundidad taladro	80 mm.
Diámetro columna	80 mm.
Dimensión mesa	315x315 mm.
Altura total	1630 mm.
Peso Neto/Bruto	78/81 kg.
Dimensiones	1410x540x310 mm.