

FORTEX®**REFERENCIA**

441593000

CÓDIGO EAN

8423640134324

ARTÍCULO

DRILLING MACHINE FTX-35C-VS VARIO 230V/F1 *P/BROCAS AUTOM.

DESCRIPCIÓN

• Belt transmission. • Spindle mounted on ball bearings. • Strong casting motors and pulleys. • Displacement of the table by zipper. • I turn the table on the 360o column. • Tilt table $\pm 45o$. • Cover opening security switch. • Machines manufactured according to CE standards. • Speed regulation by vector Frequency variedr. • Laser Pointer on the Cross. • Monofic 230V. • Automatic portfolios. • Industrial Triphasic Motor controlled by the dispenser with monophasic power. • Multichannel strap to improve traction and reduce the sound level. • Electronic speed control to save energy and greater control over the machine. • LED lighting. • High durability metal buttons. • LED tacometer. • Millimetric control of spindle descent

FORTEX®

REFERENCIA

441593000

ARTÍCULO

DRILLING MACHINE FTX-35C-VS VARIO 230V/F1 *P/BROCAS AUTOM.

DATOS TÉCNICOS

Alimentación	230V/F1
Potencia	1,5 - 2 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 700 / 0 - 3000 r/min.
Capacidad broca	32 mm.
Distancia portabrocas-columna	255 mm.
Distancia husillo-mesa	680 mm.
Distancia husillo-base	1170 mm.
Cono morse	MT3
Profundidad taladro	120 mm.
Diámetro columna	92 mm.
Dimensión mesa	475X425 mm.
Altura total	1690 mm.
Peso Neto/Bruto	111 / 116 Kg.
Dimensiones	1450X655X390 mm.