

FORTEX®

REFERENCIA

441697000

CÓDIGO EAN

8423640134355

ARTÍCULO

DRILLING MACHINE FTX-20S-ZS VARIO 230V/F1 *P/BROCAS AUTOM.

DESCRIPCIÓN

- Transmission by belts.
- Spindle mounted on ball bearings.
- Strong casting motors and pulleys.
- Displacement of the table by zipper.
- I turn the table on the 360o column.
- Turn investor.
- Thread function with automatic turning inverter with depth adjustment.
- Cover opening security switch.
- Machines manufactured according to CE standards.
- Speed regulation by vector Frequency variedr.
- Laser pointer on the cross.
- Monofic 230V power supply.
- Industrial Triphasic motor controlled by the dispenser with monophasic power.
- Multichannel strap to improve traction and reduce the sound level.
- Electric speed control to save energy and greater control over the machine.
- LED lighting.
- High durability metal buttons.
- LED tachometer.
- Millimetric control of spindle descent.
- Autopilots.

FORTEX®

REFERENCIA

441697000

ARTÍCULO

DRILLING MACHINE FTX-20S-ZS VARIO 230V/F1 *P/BROCAS AUTOM.

DATOS TÉCNICOS

Alimentación	230V/F1
Potencia	0,75 - 1 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 2100 r/min.
Capacidad broca	20 mm.
Capacidad de roscado	M12
Distancia portabrocas-columna	205 mm.
Distancia husillo-mesa	300 mm.
Distancia husillo-base	540 mm.
Cono morse	MT2
Profundidad taladro	100 mm.
Diámetro columna	70 mm.
Dimensión mesa	283X248 mm.
Altura total	1010 mm.
Peso Neto/Bruto	93 / 98 Kg.
Dimensiones	1055X610X380 mm.