

**FORTEX®****REFERENCIA**

441695000

**CÓDIGO EAN**

8423640134362

**ARTÍCULO**

DRILLING MACHINE FTX-25C-ZS VARIO 230V/F1 \*P/BROCAS AUTOM.

**DESCRIPCIÓN**

• Transmission by belts. • Spindle mounted on ball bearings. • Strong casting motors and pulleys. • Displacement of the table by zipper. • I turn the table on the 360o column. • Turn investor. • Thread function with automatic turning inverter with depth adjustment. • Cover opening security switch. • Machines manufactured according to CE standards. • Speed regulation by vector Frequency variedr. • Laser pointer on the cross. • Monofic 230V power supply. • Industrial Triphasic motor controlled by the dispenser with monophasic power. • Multichannel strap to improve traction and reduce the sound level. • Electric speed control to save energy and greater control over the machine. • LED lighting. • High durability metal buttons. • LED tachometer. • Millimetric control of spindle descent. • Autopilots.

**FORTEX®**

**REFERENCIA**

441695000

**ARTÍCULO**

DRILLING MACHINE FTX-25C-ZS VARIO 230V/F1 \*P/BROCAS AUTOM.

**DATOS TÉCNICOS**

Alimentación	230V/F1
Potencia	0,75 - 1 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 2100 r/min.
Capacidad broca	25 mm.
Capacidad de roscado	M12
Distancia portabrocas-columna	205 mm.
Distancia husillo-mesa	850 mm.
Distancia husillo-base	1160 mm.
Cono morse	MT2
Diámetro columna	80 mm.
Dimensión mesa	320X320 mm.
Profundidad taladro	100 mm.
Altura total	1630 mm.
Peso Neto/Bruto	115 / 122 Kg.
Dimensiones	1525X655X440 mm.