



☆ FORTEX®



REFERENCIA

441695000

CÓDIGO EAN

8423640134362

ARTÍCULO

Drill FTX-25C-ZS VARIO 230V / F1 * P / AUTOM BROCAS.

DESCRIPCIÓN (

• Belt transmission. • Spindle mounted on bearings to balls. • Motors and resistant castings pulleys. • Displacement of the table by zipper. • Turn from the table on the column of 360 °. • Giring inverter. • Threading function with turning inverter Automatic with depth adjustment. • Opening safety switch cover. • Machines manufactured according to EC standards. • Speed regulation by variator Vector frequency. • Laser Pointer in Cruz • 230V single-phase feeding • Industrial three-phase motor controlled by The variator with single-phase feeding • Multichannel strap to improve the Traction and reduce the Supnor level. • Electronic speed control for save energy and greater control over machine. • LED lighting • High durability metallic buttons. • Tacometer LED • Milimetric control of spindle down • Giring inverter. • Threading function with turning inverter Automatic with depth adjustment. • Automatic chuck



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

441695000



ARTÍCULO

Drill FTX-25C-ZS VARIO 230V / F1 * P / AUTOM BROCAS.

DATOS TÉCNICOS	
Feed	230v / f1
Power	0.75 - 1 kW-HP
Number of speeds	2 - Variable
Spindle	0 - 2100 R / min.
Drill	25 mm.
Threading	M12
Distance Caker-column	205 mm.
Distance spindle-table	850 mm.
Distance Husillo-Base	1160 mm.
Cone morse	Mt2
Diameter column	80 mm.
Table	320x320 mm.
Depth drill	100 mm.
Total height	1630 mm.
Net / crude weight	115/122 kg.
Dimensions	1525x655x440 mm.