

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441693000

CÓDIGO EAN

8423640134379

ARTÍCULO

Drill FTX-35C-ZS Vario 230V / F1 * P / Brackets Autom.

DESCRIPCIÓN (

• Belt transmission. • Spindle mounted on bearings to balls. • Motors and resistant castings pulleys. • Displacement of the table by zipper. • Turn from the table on the column of 360 °. • Giring inverter. • Threading function with turning inverter Automatic with depth adjustment. • Opening safety switch cover. • Machines manufactured according to EC standards. • Speed regulation by variator Vector frequency. • Laser Pointer in Cruz • 230V single-phase feeding • Industrial three-phase motor controlled by The variator with single-phase feeding • Multichannel strap to improve the Traction and reduce the Supnor level. • Electronic speed control for save energy and greater control over machine. • LED lighting • High durability metallic buttons. • Tacometer LED • Milimetric control of spindle down • Automatic chuck



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

441693000



ARTÍCULO

Drill FTX-35C-ZS Vario 230V / F1 * P / Brackets Autom.

DATOS TÉCNICOS	
Feed	230V/F1
Power	1,1 - 1,5 Kw-Hp
Number of speeds	2 - VARIABLE
Spindle	0 - 2100 r/min.
Drill	32 mm.
Threading	M16
Distance Caker-column	255 mm.
Distance spindle-table	860 mm.
Distance Husillo-Base	1200 mm.
Cone morse	MT3
Depth drill	135 mm.
Diameter column	98 mm.
Table	410X380 mm.
Total height	1770 mm.
Net / crude weight	210 / 230 Kg.
Dimensions	1595X710X610 mm.