

FORTEX®**REFERENCIA**

441693000

CÓDIGO EAN

8423640134379

ARTÍCULO

DRILLING MACHINE FTX-35C-ZS VARIO 230V/F1 *P/BROCAS AUTOM.

DESCRIPCIÓN

• Belt transmission. • Spindle mounted on ball bearings. • Strong casting motors and pulleys. • Displacement of the table by zipper. • I turn the table on the 360o column. • Turn investor. • Thread function with automatic turning inverter with depth adjustment. • Cover opening security switch. • Machines manufactured according to CE standards. • Speed regulation by vector Frequency variedr. • Laser pointer on the cross. • Monofic 230V power supply. • Industrial Triphasic motor controlled by the dispenser with monophasic power. • Multichannel strap to improve traction and reduce the sound level. • Electric speed control to save energy and greater control over the machine. • LED lighting. • High durability metal buttons. • LED tachometer. • Millimetric control of spindle descent. • Autopilots.

FORTEX®

REFERENCIA

441693000

ARTÍCULO

DRILLING MACHINE FTX-35C-ZS VARIO 230V/F1 *P/BROCAS AUTOM.

DATOS TÉCNICOS

Alimentación	230V/F1
Potencia	1,1 - 1,5 Kw-Hp
Número de velocidades	2 - VARIABLE
Velocidad husillo	0 - 2100 r/min.
Capacidad broca	32 mm.
Capacidad de roscado	M16
Distancia portabrocas-columna	255 mm.
Distancia husillo-mesa	860 mm.
Distancia husillo-base	1200 mm.
Cono morse	MT3
Profundidad taladro	135 mm.
Diámetro columna	98 mm.
Dimensión mesa	410X380 mm.
Altura total	1770 mm.
Peso Neto/Bruto	210 / 230 Kg.
Dimensiones	1595X710X610 mm.