

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441027500

CÓDIGO EAN

8423640293991

ARTÍCULO

FTX-1500X460-Top DCR 400V / F3 7.5hp + Dro + TCRE

DESCRIPCIÓN (

Industrial use lathe, designed for demanding machining work with maximum stability, safety and precision. Robust design, with Laminated and rectified prismatic guides, which ensure a high rigidity and smooth displacement of the car. Dedicated guide axis for automatic advances, optimizing efficiency in prolonged works. Safety microswitch That stops the operation when opening the pullest lid or the plate protector. Claw and turret protector, providing greater security to the operator during work. Emergency stop button, accessible y confiable ante cualquier situación crítica. Foot brake, which allows you to quickly stop the spindle without using your hands. Dial Thread Indicator, for precise and visual control of the thread passage. Race stop for longitudinal carriage feed, Ideal for repetitive and controlled machining. Manufactured under CE Normative, complying with the highest European standards of safety and quality.





☆ FORTEX®

REFERENCIA

441027500



ARTÍCULO

FTX-1500X460-Top DCR 400V / F3 7.5hp + Dro + TCRE

DATOS TÉCNICOS	
X / Y coordinate display	IF
Feed	400v / f3
Power	5.5 - 7.5 kW-HP
Change speeds	GEARS
Diameter on bench	460 mm.
Diameter over neckline	700 mm.
Diameter on car	290 mm.
Interior diameter spindle	80 mm.
Distance between points	1500 mm.
Cone	Mt7
Cone counterpoint	Mt5
Diameter counterpoint	- mm.
Journey	130 mm.
Number of speeds	12
Range speeds	25 - 1800 r.p.m.
Longitude progress rank	0.04 - 2.46 mm / rev.
Transverse progress rank	0.02 - 1.23 mm / rev.
A. Languid Longitance Intermediate car	- m / min.
A.Rapid Transversal Intermediate car	- m / min.
Range Metric Steps	24 Types / 0.5 - 20 mm.
Range inch steps	61 Types / 1-5 / 8 - 72 TPI
Diametral Steps Range	45 types / 96 - 3 1/4 d.p.
Range Modular Steps	20 Types / 0.25 - 10 m.p.
Net / crude weight	2480/2730 kg.
Dimensions	3000x1150x1680 mm.