


FORTEX®**REFERENCIA**

441030500

CÓDIGO EAN

8423640294004

ARTÍCULO


Lathe FTX-1000x460-Top DCR 400V / F3 7.5hp + Dro + TCRE

DESCRIPCIÓN

Industrial use lathe, designed for demanding machining work with maximum stability, safety and precision. Robust design, with Laminated and rectified prismatic guides, which ensure a high rigidity and smooth displacement of the car. Dedicated guide axis for automatic advances, optimizing efficiency in prolonged works. Safety microswitch That stops the operation when opening the pullest lid or the plate protector. Claw and turret protector, providing greater security to the operator during work. Emergency stop button, accesible y confiable ante cualquier situación crítica. Foot brake, which allows you to quickly stop the spindle without using your hands. Dial Thread Indicator, for precise and visual control of the thread passage. Race stop for longitudinal carriage feed, Ideal for repetitive and controlled machining. Manufactured under CE Normative, complying with the highest European standards of safety and quality.

FORTEX®
REFERENCIA

441030500


ARTÍCULO

Lathe FTX-1000x460-Top DCR 400V / F3 7.5hp + Dro + TCRE

DATOS TÉCNICOS

Visualizador de coordenadas X/Y	SI
Alimentación	400V/F3
Potencia	5.5 - 7.5 kW-HP
Cambio velocidades	ENGRANAJES
Diámetro sobre bancada	460 mm.
Diámetro sobre escote	700 mm.
Diámetro sobre carro	270 mm.
Diámetro interior husillo	80 mm.
Distancia entre puntos	1000 mm.
Cono punto	Mt7
Cono contrapunto	MT5
Diámetro contrapunto	- mm.
Recorrido contrapunto	130 mm.
Número de velocidades	12
Rango velocidades	25 - 1800 r.p.m.
Rango avance longitudinal	0.04 - 2.46 mm / rev.
Rango avance transversal	0.02 - 1.23 mm / rev.
A.Rápido longitudinal carro intermedio	- m/min.
A.Rápido transversal carro intermedio	- m/min.
Rango pasos métricos	24 Types / 0.5 - 20 mm.
Rango pasos pulgadas	61 Types / 1-5 / 8 - 72 TPI
Rango pasos diametrales	45 Types / 96 - 3-1 / 4 d.p.
Rango pasos modulares	20 Types / 0.25 - 10 m.p.
Peso Neto/Bruto	2270/2470 kg.
Dimensiones	2500x1150x1680 mm.