

## FICHA TÉCNICA DE PRODUCTO

#### **☆ FORTEX**®



REFERENCIA

441515000

CÓDIGO EAN

8423640964181

ARTÍCULO

Drill Gears FTX-55-TEC XPRO \* 400V / F3 + Jaw

### DESCRIPCIÓN (

Robust and versatile equipment, designed for machining work that require precision, stability and security in prolonged operations. Spindle mounted on ball bearings, which guarantees a smooth, durable performance and with excellent concentricity. Motors and resistant casting pulleys, Ideally to support continuous efforts and provide a long service life. Displacement of the table by zipper system, which ensures controlled and consistent movements.  $360^{\circ}$  table turn on the spine, allowing maximum flexibility in the positioning of the piece. Tilt table  $\pm$  45 °, Ideal for angled jobs without the need for complex external configurations. Electrical Components Siemens, synonymous with quality, reliability and compliance with international regulations. Giring inverter (in R + L models), which allows you to easily select the spindle rotation direction. Safety switch with automatic stop when opening the lid, reinforcing the protection of the operator. Manufacture according to EC standards, guaranteeing security, efficiency and compliance with European standards.



# FICHA TÉCNICA DE PRODUCTO

## **☆ FORTEX**®

REFERENCIA

441515000



## ARTÍCULO

Drill Gears FTX-55-TEC XPRO \* 400V / F3 + Jaw

| DATOS TÉCNICOS          |                                |
|-------------------------|--------------------------------|
| Feed                    | 400v / f3                      |
| Power                   | 2.2 / 2,8 - 3 / 3,75 kW-HP     |
| Transmission            | Gears                          |
| Number of speeds        | 12                             |
| Velocidad1              | 42 - 1865 r.p.m.               |
| Maximum capacity drill  | 50 mm.                         |
| Threading               | M32                            |
| Distance Caker-column   | 360 mm.                        |
| Cone morse              | Mt4                            |
| Depth drill             | 180 mm.                        |
| Slot size in T          | 2x14 / 2x16 mm.                |
| Distance Husillo-Base   | 1205 mm.                       |
| Distance spindle-table  | 600 mm.                        |
| Max. work table         | 525 mm.                        |
| Diameter column         | 170 mm.                        |
| Base dimension          | 575x565 mm.                    |
| Table                   | 370x500 mm.                    |
| Tilt                    | 45th                           |
| Hausyl advance          | 0.07 / 0.15 / 0.26 / 0.4 mm./r |
| Refrigeration equipment | IF                             |
| Motorized working table | IF                             |
| Total height            | - mm.                          |
| Net / crude weight      | 676/758 kg.                    |
| Dimensions              | 700x1150x2200 mm.              |