FORTEX®



## REFERENCIA

441525000

## CÓDIGO EAN

8423640964167

## ARTÍCULO

Gear Drilling Machine FTX-35-TEC XPRO * 400V / F3 + Jaw

## DESCRIPCIÓN

Industrial equipment designed to offer Maximum precision, low noise level and high reliability in continuous machining work.Silent gearbox, which significantly reduces the sound emission during the operation, ideal for long work environments.Automatic spindle progress, optimizing productivity and uniformity in processes.High precision spindle and cane, guaranteeing excellent concentricity and finishing quality.Built-in refrigeration equipment, which allows you to maintain stable work temperatures and prolongs the useful of tools.Tilt table ± 90º, which provides versatility for work at different angles and positions.Changing speeds by levers, fast and comfortable drive, ideal for frequent settings.Electrical Components Siemens, Synonym of quality, safety and durability.Turnover, to easily change the direction of rotation of the spindle.Electromagnetic clutch, which allows a smooth and precise coupling of the spindle without stopping the engine.Manufacture according to EC standards, complying with European safety and quality standards.

FORTEX®



REFERENCIA

441525000

ARTÍCULO

Gear Drilling Machine FTX-35-TEC XPRO * 400V / F3 + Jaw

| DATOS TÉCNICOS | |
|---|---|
| **Alimentación** | 400V/F3 |
| **Potencia** | 1.5 / 2,2 - 2/3 kW-HP |
| **Transmisión** | Engranajes |
| **Número de velocidades** | 12 |
| **Velocidad1** | 70 - 2600 r.p.m. |
| **Capacidad máxima broca** | 35 mm. |
| **Capacidad de roscado** | M24 |
| **Distancia portabrocas-columna** | 330 mm. |
| **Cono morse** | MT4 |
| **Profundidad taladro** | 150 mm. |
| **Tamaño ranura en T** | 2X14 / 2X16 mm. |
| **Distancia husillo-base** | 1050 mm. |
| **Distancia husillo-mesa** | 610 mm. |
| **Recorrido máx. mesa de trabajo** | 540 mm. |
| **Diámetro columna** | 140 mm. |
| **Dimensión base** | 370x360 mm. |
| **Dimensión mesa** | 374x374 mm. |
| **Inclinación mesa** | 45º |
| **Avance husilo** | 0,1 / 0,2 / 0,3 mm./r |
| **Equipo refrigeración** | SI |
| **Altura total** | - mm. |
| **Peso Neto/Bruto** | 539/621 kg. |
| **Dimensiones** | 700X1150X2200 mm. |