

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441542000

CÓDIGO EAN

8423640964174

ARTÍCULO

Drill Gear FTX-45-TEC XPRO * 400V / F3 + Jaw

DESCRIPCIÓN (

Industrial equipment designed to offer Maximum precision, low noise level and high reliability in continuous machining work. Silent gearbox, which significantly reduces the sound emission during the operation, ideal for long work environments. Automatic spindle progress, optimizing productivity and uniformity in processes. High precision spindle and cane, guaranteeing excellent concentricity and finishing quality. Built-in refrigeration equipment, which allows you to maintain stable work temperatures and prolongs the useful of tools. Tilt table \pm 90°, which provides versatility for work at different angles and positions. Changing speeds by levers, fast and comfortable drive, ideal for frequent settings. Electrical Components Siemens, Synonym of quality, safety and durability. Turnover, to easily change the direction of rotation of the spindle. Electromagnetic clutch, which allows a smooth and precise coupling of the spindle without stopping the engine. Manufacture according to EC standards, complying with European safety and quality standards.



FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®

REFERENCIA

441542000



ARTÍCULO

Drill Gear FTX-45-TEC XPRO * 400V / F3 + Jaw

DATOS TÉCNICOS	
Feed	400v / f3
Power	2.2 / 2,8 - 3 / 3,75 kW-HP
Transmission	Gears
Number of speeds	12
Velocidad1	42 - 2050 r.p.m.
Maximum capacity drill	40 mm.
Threading	M28
Distance Caker-column	360 mm.
Cone morse	Mt4
Depth drill	180 mm.
Slot size in T	2x14 / 2x16 mm.
Distance Husillo-Base	1215 mm.
Distance spindle-table	600 mm.
Max. work table	560 mm.
Diameter column	160 mm.
Base dimension	575x565 mm.
Table	370x500 mm.
Tilt	45th
Hausyl advance	0.07 / 0.15 / 0.26 / 0.4 mm./r
Refrigeration equipment	IF
Motorized working table	IF
Total height	- mm.
Net / crude weight	658/740 kg.
Dimensions	700x1150x2200 mm.