

FICHA TÉCNICA DE PRODUCTO

☆ FORTEX®



REFERENCIA

441335000

CÓDIGO EAN

8423640963825

ARTÍCULO

Universal Ftx-130-FC * 400V-F3

DESCRIPCIÓN (

High performance milling machine designed for precision work in industrial environments. Its robust construction and quality components guarantee reliability, versatility and precision in each operation. Gear transmission, which provides greater power, stability and durability in high effort jobs. Robust design with front attack, Ideal for demanding machining and continuous operation. High precision coordinate table, which allows an exact positioning of the piece for fine and repetitive finishes. Column with Milan tail guides, Ensuring structural rigidity and a soft movement of the head. Adjustable milling head, adaptable to different angles and types of machining. Automatic advances in the X, Y and Z axes included as standard, for a more efficient, accurate and less dependent operation of the operator. Manufactured according to EC standards, complying with European safety and industrial quality standards.





☆ FORTEX®

REFERENCIA

441335000



ARTÍCULO

Universal Ftx-130-FC * 400V-F3

DATOS TÉCNICOS	
Feed	400v / f3
Power	3 - 4 kW-HP
Transmission	Gears
Number of speeds	11 (V) - 12 (H)
Speed	45 - 1660 (V) / 38 - 1300 (H) m.p.m.
Coordinator X/Y/Z	IF
Table forward (X, Y, Z)	22 - 420/8 (X,Y), 422 (Z) mm/min
Fast forward (X, Y, Z)	1200 (X,Y), 422 (Z) mm/min
Maximum capacity drill	13 - 28 mm.
Tilt of the head	360º
Load capacity	250 (mesa) Kg.
Maximum diameter of vertical milling	25 mm.
Maximum diameter of horizontal milling	125 mm.
Distance Spin-column	200 - 760 (V), 30 - 450 (H) mm.
Distance spindle-table	200 - 640 (V) mm.
Cone morse	Iso40
Longitudinal tour (x)	1000 mm.
Transversal tour (Y)	300 mm.
Vertical travel (Z)	440 mm.
Slot size in T	5x14 mm.
Total height	- mm.
Table	1320x320 mm.
Net / crude weight	2100 / 2300 Kg.
Dimensions	2020X1710X2000 mm.