

**FORTEX®**

**REFERENCIA**

441103000

**CÓDIGO EAN**

8423640093232

**ARTÍCULO**

Lathe FTX-800X300-TO VARIO 230V / F1 with pedestal

**DESCRIPCIÓN**

This high precision lathe is designed to offer professional performance, mechanical reliability and operational security. Its configuration includes: Automatic advance of longitudinal and cross carriage, allowing more efficient and accurate operations without constant manual intervention. Double "V" guides, temperate and rectified, which guarantee greater durability and precision in the sliding of the cars. Precision spindle mounted on conical bearings, which provides excellent stability and concentricity during machining. Adjustable plywood To eliminate clearances in the guides, ensuring greater rigidity and accuracy. Easy-time counterpoint, with graduated cylinder Metric and Imperial System, Ideal for international or precision jobs. Independent threaded bar For functions of thread, avoiding premature wear from other components. Brushless engine, which offers quieter, efficient and maintenance-free operation. Reversible threaded bar, allowing Threaded threaded, expanding the versatility of the lathe. Large intermediate car, with Two slots in t To facilitate the clamping of special accessories or tools. Security microswitches on the pullestick and protector of the dish, which Automatically interrupt operation When he was opened. Claw and turret protectors, providing greater safety to the operator. Emergency stop button, accesible y confiable ante cualquier situación crítica. Dial Thread Indicator, for precise control in threading operations. Manufactured under CE Normative, complying with European safety and quality standards.

**ARTÍCULO**

Lathe FTX-800X300-TO VARIO 230V / F1 with pedestal

**DATOS TÉCNICOS**

Visualizador de coordenadas X/Y	NO
Alimentación	230V/F1
Potencia	1,5 - 2 Kw-Hp
Cambio velocidades	VARIABLE
Diámetro sobre bancada	300 mm.
Diámetro sobre escote	- mm.
Diámetro sobre carro	190 mm.
Ancho de bancada	180 mm.
Diámetro interior husillo	38 mm.
Distancia entre puntos	800 mm.
Cono punto	MT5
Cono contrapunto	MT3
Diámetro contrapunto	- mm.
Recorrido contrapunto	70 mm.
Número de velocidades	Variable
Rango velocidades	80 - 2000 r.p.m.
Rango avance longitudinal	0,085 - 0,832 mm/rev.
Rango avance transversal	0.01 - 0.1 mm/rev.
A.Rápido longitudinal carro intermedio	- m/min.
A.Rápido transversal carro intermedio	- m/min.
Rango pasos métricos	18 TIPOS / 0,2 - 3,5 mm.
Rango pasos pulgadas	18 TIPOS / 8 - 56 tpi
Rango pasos diametrales	- d.p.
Rango pasos modulares	- m.p.
Peso Neto/Bruto	260 kg.
Dimensiones	1500x720x690 mm.