

A FORTEX**REFERENCIA**

441103000

CÓDIGO EAN

8423640093232

ARTÍCULO

Lathe FTX-800X300-TO VARIO 230V / F1 with pedestal

DESCRIPCIÓN

This high precision lathe is designed to offer professional performance, mechanical reliability and operational security. Its configuration includes: Automatic advance of longitudinal and cross carriage, allowing more efficient and accurate operations without constant manual intervention. Double "V" guides, temperate and rectified, which guarantee greater durability and precision in the sliding of the cars. Precision spindle mounted on conical bearings, which provides excellent stability and concentricity during machining. Adjustable plywood To eliminate clearances in the guides, ensuring greater rigidity and accuracy. Easy-time counterpoint, with graduated cylinder Metric and Imperial System, Ideal for international or precision jobs. Independent threaded bar For functions of thread, avoiding premature wear from other components. Brushless engine, which offers quieter, efficient and maintenance-free operation. Reversible threaded bar, allowing Threaded threaded, expanding the versatility of the lathe. Large intermediate car, with Two slots in t To facilitate the clamping of special accessories or tools. Security microswitches on the pulleystick and protector of the dish, which Automatically interrupt operation When he was opened. Claw and turret protectors, providing greater safety to the operator. Emergency stop button, accesible y confiable ante cualquier situación crítica. Dial Thread Indicator, for precise control in threading operations. Manufactured under CE Normative, complying with European safety and quality standards.

ARTÍCULO

Lathe FTX-800X300-TO VARIO 230V / F1 with pedestal

DATOS TÉCNICOS

Coordinate viewer X/Y	NO
Alimentación	230V/F1
Potencia	1,5 - 2 Kw-Hp
Change speeds	VARIABLE
Diameter on bench	300 mm.
Diameter on neckline	- mm.
Diameter on cart	190 mm.
Banking width	180 mm.
Inner diameter spindle	38 mm.
Distance between points	800 mm.
Point	MT5
Cone contrapoint	MT3
Diameter counterpoint	- mm.
Tour counterpoint	70 mm.
Número de velocidades	VARIABLE
Spindle speed range	80 - 2000 r.p.m.
Longitudinal forward range	0,085 - 0,832 mm/rev.
Cross-sectional forward range	0.01 - 0.1 mm/rev.
A. Rapid longitudinal intermediate car	- m/min.
A. Cross-sectional carriage	- m/min.
Range metric steps	18 TIPOS / 0.2 - 3.5 mm.
Rank inches	18 TIPOS / 8 - 56 tpi
Range diametric steps	- d.p.
Range modular steps	- m.p.
Peso Neto/Bruto	260 kg.
Dimensiones	1500x720x690 mm.