

FORTEX®**REFERENCIA**

441537000

CÓDIGO EAN

8423640965294

ARTÍCULO

FTX-40-TEC SPRO * 400V/F3

DESCRIPCIÓN

High precision milling drill equipped with silent gearbox and automatic spindle advance. It incorporates thread function, tiltable table $\pm 45^\circ$ and speed change via levers. It has turn inverter, electromagnetic clutch and cooling system. Manufactured in accordance with CE standards to ensure optimal safety and performance.

FORTEX®

REFERENCIA

441537000

ARTÍCULO

FTX-40-TEC SPRO * 400V/F3

DATOS TÉCNICOS

Alimentación	400V/F3
Potencia	0.85/1.5 - 1.1/2 Kw-Hp
Transmisión	Engranajes
Número de velocidades	18
Velocidad	50 - 1450 m.p.m.
Capacidad máxima broca	40 mm.
Capacidad de roscado	M24
Distancia portabrocas-columna	350 mm.
Cono morse	MT4
Profundidad taladro	180 mm.
Tamaño ranura en T	2X18, 2X18 mm.
Distancia husillo-base	1210 mm.
Distancia husillo-mesa	770 mm.
Recorrido máx. mesa de trabajo	560 mm.
Diámetro columna	160 mm.
Dimensión base	730X500 mm.
Dimensión mesa	560X560 mm.
Inclinación mesa	45º
Avance husilo	0.10/0.20 mm./r
Equipo refrigeración	SI
Altura total	- mm.
Peso Neto/Bruto	465 / 550 Kg.
Dimensiones	2290X630X1090 mm.