



REFERENCIA

383242800

CÓDIGO EAN

8011399035469

ARTÍCULO

MIG / MAG INVERTER MIGA 380 230V / F1 with ACC.

DESCRIPCIÓN

MIGA 380 supplies 200 AMPERIOS from DC Continue (CC). The supply voltage is single-phase 230 volts. Has low energy consumption and It can be used with low installed power (3 kW) or connected to a generator (see Technical Data Table). Supports wire coils with a diameter of 300/200 mm. The synergistic or manual MIG process allows us to weld many metals as steel, Stainless steel, Aluminum and perform strong welding with copper-silicon wires or copper-aluminum.


REFERENCIA

383242800


ARTÍCULO

MIG / MAG INVERTER MIGA 380 230V / F1 with ACC.

DATOS TÉCNICOS

Alimentación	230V/F1
Power consumed: 60% / max.	2.8 / 4.5 kW
Fusible	16 Amp.
Generador compatible	7 kW / kVA.
Regulación de soldar	10 - 200 MIG-TIG / 10-160 MMA AMP.
Servicio EN60974-1 (40°C)	MIG-TIG 180A-25% / MMA 150A-25% MIG-TIG 100A-60% / MMA 100A-60% AMP.
Tensión en vacío	86 Volt.
Diámetro hilo acero	0.6 - 0.8 - 0.9 - 1.0 mm.
Diameter thread stainless steel.	0.8 - 1.0 mm.
Diameter thread aluminum	0.8 - 1.0 - 1.2 mm.
Diameter tubular thread	0.8 - 0.9 - 1.0 - 1.2 mm.
Ø Bobina hilo	200 - 300 mm.
Electrodos utilizables	MMA 1,6-4.0 / TIG 1.0-4.0 Ø mm.
Connector Dinse	25 mm.
Antorcha EURO	SI
Peso Neto/Bruto	25.5 / 30 kg.
Dimensión aparato	777 x 407 x 792 mm.
Dimensiones embalaje	800 x 300 x 650 mm.