



REFERENCIA

383247100

CÓDIGO EAN

8011399035391

ARTÍCULO

MIG / MAG INVERTER EASY JOB 525E LAB 230V / F1 with ACC.

DESCRIPCIÓN

EasyJob 525E LAB is the perfect synergic multiprocess multiprocess solder for anyGarage and well-equipped workshop. EasyJob 525E Lab supplies 250 A in continuous current (CC). The supply voltage It is single-phase 230 volts. It offers 4 welding processes always by hand: MIG / MAG, FLUX, MMA and TIG LIFT. In MiR / MAG and Flux modes, easyjob 525E Lab is Perfect for welding steel, stainless steel, aluminum and to use wires Strong welding



REFERENCIA

383247100



ARTÍCULO

MIG / MAG INVERTER EASY JOB 525E LAB 230V / F1 with ACC.

DATOS TÉCNICOS

Alimentación	230V/F1
Power consumed: 60% / max.	3.3 / 6.3 kW
Fusible	25 AMP.
Generador compatible	9 kW / kva.
Regulación de soldar	10 - 250 MIG-TIG / 10-200 MMA AMP.
Servicio EN60974-1 (40°C)	MIG-TIG 220A-20% / MMA 180A-25% MIG-TIG 120A-60% / MMA 120A-60% AMP.
Tensión en vacío	96 Volt.
Diámetro hilo acero	0.6 - 0.8 - 0.9 - 1.0 - 1.2 mm.
Diameter thread stainless steel.	0.8 - 1.0 mm.
Diameter thread aluminum	0.8 - 1.0 - 1.2 mm.
Diameter tubular thread	0.8 - 0.9 - 1.0 - 1.2 mm.
Ø Bobina hilo	200 - 300 mm.
Electrodos utilizables	MMA 1,6-4.0 / TIG 1.0-4.0 Ø mm.
Connector Dinse	50 mm.
Antorcha EURO	SI
Peso Neto/Bruto	30/35 kg.
Dimensión aparato	777 x 407 x 792 mm.
Dimensiones embalaje	800 x 300 x 650 mm.