



**REFERENCIA**

383250200

**CÓDIGO EAN**

8011399034790

**ARTÍCULO**

MIG / MAG Inverter JOB 222 PD Lab 230v / F1 with ACC.

**DESCRIPCIÓN**

Job 222 PD Lab is the ideal welding machine for the craftsman and professional that You need different welding processes in a single system: MIG / MAG, FLUX, MMA And Tig Lift. JOB 222 PD LAB supplies 220 AMPERIOS of DC25 (CC). The Feed voltage is single-phase 230 volts. Can be connected to an engineGenerator (see Technical Data Table).MIG / MAG pressed and double-pressed for steel welding, stainless steel, Aluminum and for use of strong welding wires. The synergistic control It is extremely effective.



## REFERENCIA

383250200



## ARTÍCULO

MIG / MAG Inverter JOB 222 PD Lab 230v / F1 with ACC.

### DATOS TÉCNICOS

|                                  |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| Alimentación                     | 230V/F1                                                              |
| Power consumed: 60% / max.       | 3.3 / 6.3 kW                                                         |
| Fusible                          | 25 AMP.                                                              |
| Generador compatible             | 9 kW / kva.                                                          |
| Regulación de soldar             | 10 - 220 MIG-TIG / 10-160 MMA AMP.                                   |
| Servicio EN60974-1 (40°C)        | MIG-TIG 220A-20% / MMA 160A-30% MIG-TIG 140A-60% / MMA 130A-60% AMP. |
| Tensión en vacío                 | 88 Volt.                                                             |
| Diámetro hilo acero              | 0.6 - 0.8 - 1.0 mm.                                                  |
| Diameter thread stainless steel. | 0.8 - 1.0 mm.                                                        |
| Diameter thread aluminum         | 0.8 - 1.0 - 1.2 mm.                                                  |
| Diameter tubular thread          | 0.8 - 0.9 - 1.2 mm.                                                  |
| Ø Bobina hilo                    | 200 - 300 mm.                                                        |
| Electrodos utilizables           | MMA 1,6-4.0 / TIG 1.0-4.0 Ø mm.                                      |
| Connector Dinse                  | 25 mm.                                                               |
| Antorcha EURO                    | SI                                                                   |
| Peso Neto/Bruto                  | 14.6 / 19.4 kg.                                                      |
| Dimensión aparato                | 556 x 268 x 438 mm.                                                  |
| Dimensiones embalaje             | 605 x 325 x 495 mm.                                                  |