



REFERENCIA

383250600

CÓDIGO EAN

8011399035476

ARTÍCULO

MIG / MAG INVERACT JOB TRIO 220 LAB 230V / F1 with ACC.

DESCRIPCIÓN

Job Trio 220 Lab is equipped with 3 welding torches simultaneously Steel, aluminum or strong welding (CUI3 / EQU8). Simply press the button on one of the torches to recover the program Welding set. Job Trio 220 Lab supplies 220 amps in continuous current (CC). Tension Feeding is single-phase 230 volt. Job Trio 220 Lab offers 3 welding processes always by hand: Mig / Mag, MMA and TIG LIFT.



REFERENCIA

383250600



ARTÍCULO

MIG / MAG INVERACT JOB TRIO 220 LAB 230V / F1 with ACC.

DATOS TÉCNICOS

Alimentación	230V/F1
Power consumed: 60% / max.	3.3 / 6.3 kW
Fusible	25 AMP.
Generador compatible	9 kW / kva.
Regulación de soldar	10 - 220 MIG-TIG / 10-160 MMA AMP.
Servicio EN60974-1 (40°C)	MIG-TIG 220A-20% / MMA 140A-30% MIG-TIG 140A-60% / MMA 130A-60% AMP.
Tensión en vacío	85 Volt.
Diámetro hilo acero	0.6 - 0.8 - 1.0 mm.
Diameter thread stainless steel.	0.8 - 1.0 mm.
Diameter thread aluminum	0.8 - 1.0 - 1.2 mm.
Ø Bobina hilo	200 - 300 x 3 mm.
Electrodos utilizables	MMA 1,6-4,0 / TIG 1.0-3.2 Ø mm.
Connector Dinse	25 mm.
Antorcha EURO	lf x 3
Peso Neto/Bruto	50/59 kg.
Dimensión aparato	860 x 560 x 1000 mm.
Dimensiones embalaje	795 x 300 x 830 mm.