



REFERENCIA

383250900

CÓDIGO EAN

8011399035162

ARTÍCULO

MIG / MAG INVERACT JOB DUO 220 LAB 230V / F1 with ACC.

DESCRIPCIÓN

Multiprocess generator Sinnergistic Mig / Mag welded and double pressed with two torches. Dedicated to body work, for exceptional results in aluminum of low thickness and stainless steel. Job Duo 220 Lab is equipped with two welding torches simultaneously Steel, aluminum or strong welding (CUSI3 / EQU8). Simply press the button on one of the torches to recover the program of Welding configured. MIG / MAG pressed and double-pressed for steel welding, stainless steel, aluminum and for the use of strong welding wires.



REFERENCIA

383250900



ARTÍCULO

MIG / MAG INVERACT JOB DUO 220 LAB 230V / F1 with ACC.

DATOS TÉCNICOS

Alimentación	230V/F1
Power consumed: 60% / max.	3.3 / 6.3 kW
Fusible	25 AMP.
Generador compatible	9 kW / kva.
Regulación de soldar	10 - 220 MIG-TIG / 10-160 MMA AMP.
Servicio EN60974-1 (40°C)	MIG-TIG 220A-20% / MMA 160A-30% MIG-TIG 140A-60% / MMA 130A-60% AMP.
Tensión en vacío	88 Volt.
Diámetro hilo acero	0.6 - 0.8 - 1.0 mm.
Diameter thread stainless steel.	0.8 - 1.0 mm.
Diameter thread aluminum	0.8 - 1.0 - 1.2 mm.
Ø Bobina hilo	200 - 300 x 2 mm.
Electrodos utilizables	MMA 1,6-4,0 / TIG 1.0-3.2 Ø mm.
Connector Dinse	25 mm.
Antorcha EURO	lf x 2
Peso Neto/Bruto	48.5 / 55.5 kg.
Dimensión aparato	860 x 560 x 1000 mm.
Dimensiones embalaje	795 x 300 x 830 mm.