

**REFERENCIA**

384111000

CÓDIGO EAN

8011399034349

ARTÍCULO

Plasma Inverter I-PAC 340 230V / F1 with ACC.

DESCRIPCIÓN

I-PAC 340 supplies 35 amps and is able to cut with good quality up to 8 mm in sweet steel. If there are no particular quality requirements, the machine Separate up to 12 mm thick. The supply voltage is single-phase 230 volts. Thanks to his bass Energy consumption can be used with reduced installed power; It can Connect to a generator engine (see Technical Data Table). The machine requires 115 liters per minute of compressed air.



REFERENCIA

384111000



ARTÍCULO

Plasma Inverter I-PAC 340 230V / F1 with ACC.

DATOS TÉCNICOS

Alimentación	230V-F1
Power consumed: 60% / max.	2.7 / 3.9 kW
Fusible	16 Amp.
Generador compatible	6 kW / kva.
Cutting current	5 - 35 amp.
Servicio EN60974-1 (40°C)	35A-30% / 25A-60% / 20A-100% AMP.
Tensión en vacío	410 Volt.
Pressure Air Bar.	3.5 - 5 bar.
Consumo de aire	115 m / h
Cutting capacity	8/12 mm.
Integrated compressor	NOT
Peso Neto/Bruto	6.7 / 8 kg.
Dimensión aparato	480 x 160 x 273 mm.
Dimensiones embalaje	495 x 205 x 400 mm.